



MLP1-230L-W



Specially developed spd with combined protection for 2-phase power supply (control phase):

- Many variants available depending on application
- With screw terminals or cable wiring
- IP65 versions
- For protection class I or II application
- Developed for Uoc: 10 kV and I_{max}: 10 kA for highest outdoor requirements according to IEEE & ANSI
- Optical error signalling



	Electrical Characteristics																																																													
 <p>V : Varistor Ft: Thermal fuse GSG: Specific gas tube LED: Status indicator t*: Thermal system disconnection</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>2+3</td></tr> <tr><td>Network</td><td></td><td>220-240 V Single-phase</td></tr> <tr><td>AC system</td><td></td><td>TT-TN</td></tr> <tr><td>Nominal line voltage</td><td>U_n</td><td>230-277 Vac</td></tr> <tr><td>Max. AC operating voltage</td><td>U_c</td><td>305 Vac</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>10 MHz</td></tr> <tr><td>Max. load current</td><td>I_L</td><td>2.5 A</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>I_{pe}</td><td>None</td></tr> <tr><td>Follow current</td><td>I_f</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>I_n</td><td>5 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>10 kA</td></tr> <tr><td>Total Maximum discharge current max. total withstand @ 8/20 μs</td><td>I_{max Total}</td><td>20 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td><td>U_{oc}</td><td>10 kV / 5 kA</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>10 kV / 10 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level L/N @ I_n (8/20μs)</td><td>Up L/N</td><td>1.5 kV</td></tr> <tr><td>Protection level L/PE @ I_n (8/20μs)</td><td>Up L/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I_{scrc}</td><td>10 000 A</td></tr> </table>		SPD type		2+3	Network		220-240 V Single-phase	AC system		TT-TN	Nominal line voltage	U _n	230-277 Vac	Max. AC operating voltage	U _c	305 Vac	Max. frequency	f max.	10 MHz	Max. load current	I _L	2.5 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Residual Current Leakage current to Ground	I _{pe}	None	Follow current	I _f	None	Nominal discharge current 15 x 8/20 μs impulses	I _n	5 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	10 kA	Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max Total}	20 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U _{oc}	10 kV / 5 kA	Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA	Protection mode(s)		Common/Differential mode	Protection level L/N @ I _n (8/20μs)	Up L/N	1.5 kV	Protection level L/PE @ I _n (8/20μs)	Up L/PE	1.5 kV	Admissible short-circuit current	I _{scrc}	10 000 A
SPD type		2+3																																																												
Network		220-240 V Single-phase																																																												
AC system		TT-TN																																																												
Nominal line voltage	U _n	230-277 Vac																																																												
Max. AC operating voltage	U _c	305 Vac																																																												
Max. frequency	f max.	10 MHz																																																												
Max. load current	I _L	2.5 A																																																												
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																																												
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																																												
Residual Current Leakage current to Ground	I _{pe}	None																																																												
Follow current	I _f	None																																																												
Nominal discharge current 15 x 8/20 μs impulses	I _n	5 kA																																																												
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	10 kA																																																												
Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max Total}	20 kA																																																												
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U _{oc}	10 kV / 5 kA																																																												
Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA																																																												
Protection mode(s)		Common/Differential mode																																																												
Protection level L/N @ I _n (8/20μs)	Up L/N	1.5 kV																																																												
Protection level L/PE @ I _n (8/20μs)	Up L/PE	1.5 kV																																																												
Admissible short-circuit current	I _{scrc}	10 000 A																																																												
	Mechanical Characteristics																																																													
	Technology																																																													
	Connection to Network																																																													
	Mounting																																																													
	Housing material																																																													
	Operating temperature																																																													
	Protection rating																																																													
	Failsafe mode																																																													
	Disconnection indicator																																																													
	Voltage/operating indicator																																																													
	Remote signaling of disconnection																																																													
	Dimensions																																																													
	Weight																																																													
	Disconnectors																																																													
	Thermal disconnector																																																													
	Installation ground fault breaker																																																													
	Standards																																																													
	Standards compliance																																																													
	Part number																																																													
	711211																																																													